

4. The optical pickup device as claimed in claim 2, wherein said lens holder comprises:

- a proximal end part actuated by said actuator;
- a distal end part extending from said proximal
- 5 end part in a direction away from said support part;
- connection parts provided on both sides of said proximal end part and connected to the distal ends of said elastic supporters; and
- a concave part to which said weight part is
- 10 bonded, the concave part being formed in a tip part formed on a distal end side of said distal end part.

15

5. The optical pickup device as claimed in claim 1, wherein said weight part is formed of a rigid body and is bonded to a position farther in a direction toward a distal end side of said lens holder than a
- 20 position to which said lens is attached.

25

6. The optical pickup device as claimed in claim 1, wherein said lens holder comprises:

- a first part holding said actuator;
- a second part extending from said first part and holding said lens; and
- 30 a concave part formed in an end part of said second part, the end part being on a side opposite to that of said first part,
- wherein said weight part is fitted into said

00004932 112204

concave part.

5

7. The optical pickup device as claimed in claim 6, wherein said weight part and said concave part has a rectangular shape.

10

8. The optical pickup device as claimed in claim 1, wherein said weight part is formed of a material having a specific gravity higher than that of said lens holder.

20

9. The optical pickup device as claimed in claim 1, wherein said weight part is formed of a material having stiffness higher than that of said lens holder.

25

10. The optical pickup device as claimed in claim 1, wherein said weight part is formed of a metal material.

30

00993-4204
T0327 2264660

5

20

25

30

oppose said lens holder; and

a plurality of elastic supporters each extending
along said lens holder and having a distal end engaging
said lens holder and a proximal end connected to said
5 support part.

10 15. The optical pickup device as claimed in
claim 14, wherein said elastic supporters are cantilever
springs.

15

16. The optical pickup device as claimed in
claim 14, wherein said lens holder comprises:

a proximal end part actuated by said actuator;
20 a distal end part extending from said proximal
end part in a direction away from said support part;
connection parts provided on both sides of said
proximal end part and connected to the distal ends of said
elastic supporters; and
25 a concave part to which said weight part is
bonded, the concave part being formed in a tip part formed
on a distal end side of said distal end part.

30

17. The optical pickup device as claimed in
claim 12, wherein said weight part is formed of a rigid

000493-1304
FOBET 2E6660

5

18. An optical pickup device comprising:
a lens for projecting a light onto a recording
10 medium;
a lens holder elastically supported by a frame
and holding said lens;
an actuator mounted in and driving said lens
holder;
15 a weight part balanced with a weight of said
actuator; and
an adhesive agent fixing said weight part to
said lens holder, the adhesive agent having
viscoelasticity such that said weight part serves as a
20 dynamic vibration absorber.